

HONDA

POWER PRODUCTS

BRUSHCUTTERS

علف زن های موتوروی هوندا

	SPECIFICATIONS	HONDA UMK435	
ENGINE	TYPE	U2T	UMT
	ENGINE	Gasoline Engine, 4-stroke, overhead camshaft valve, single cylinder	
	TOTAL DISPLACEMENT	35.8 CC.	
	BORE AND STROKE	39 X 30 mm.	
	MAX. HORSEPOWER	1.2 kW (1.6HP) at 7,000 rpm	
	MAX. TORQUE	1.9 N.m (0.19 kg.m.) at 5,500 rpm	
	COMPRESSION RATIO	8.0 : 1	
	FUEL CONSUMPTION	360 g/kwh (265 g/Hph)	
	COOLING SYSTEM	Forced air	
	IGNITION SYSTEM	Transistorized magneto	
	SPARK PLUG	CM5H / CMR5H (NGK)	
	CARBURETOR	Diaphragm type	
	AIR CLEANER	Dry type	
	LUBRICATION SYSTEM	Rotary Slinger Pumping Spray	
	OIL CAPACITY	0.1 L	
	AMBIENT TEMPERATURE DURING OPERATION	-5 degree Celsius to 40 degree Celsius (23 degree Fahrenheit to 104 degree Fahrenheit)	
	STARTING SYSTEM	Recoil starter	
	STOPPING SYSTEM	Ignition primary circuit ground	
	FUEL USED	Regular unleaded gasoline with a pump octane number 86 or higher	
	FUEL TANK CAPACITY	0.65 L	
SHAFT	OVERALL WIDTH (mm.)	637	
	OVERALL HEIGHT (mm.)	444	
	OVERALL LENGTH (mm.)	1928	1922
	BLADE DIAMETER (mm.)	305 (2 Blade 12 inch)	285 (Mowing set)
	NET WEIGHT (kg.)	8.45	9.1

